

# Microline Dot Matrix Printer range

## 24-Pin Dot Matrix Printer range

						
<b>Narrow carriage</b>		<b>ML3390</b>	<b>ML390FB</b>	<b>ML6300FB</b>	<b>ML5590</b>	
<b>Wide carriage</b>		<b>ML3391</b>			<b>ML5591</b>	<b>ML395 B/C</b>
<b>Print Head</b>	Number of pins	24	24	24	24	24
	Fastest print speed (cps)	390	270	450	473	607
	Utility/LQ print speed at 10cpi (cps)	260/87	225/75	300/100	315/105	405/135
	Number of copies	1+4	1+4	1+5	1+4	1+3
	Resolution (dpi)	360 x 360	240 x 360	360 x 360	360 x 360	240 x 360
<b>Paper feed</b>	Feed method	Friction feed Push tractor	Friction feed Front push tractor	Friction feed Push tractor	Friction feed Push tractor	Friction feed Push tractor
	Tractor options	Top pull Bottom push	N/A	N/A	Top pull Bottom push	Top pull Bottom power push
	Cut sheet feeder options	Single & dual	Single bin	N/A	Single & dual	Single & dual
<b>Column width (characters)</b>	Narrow carriage version at 10cpi	80	106	106	80	N/A
	Wide carriage version at 10cpi	136	N/A	N/A	136	136
	Compressed mode (narrow/wide)	160/272	212	212	160/272	272
<b>Interfaces &amp; Emulations</b>	Number of fonts	10 + barcodes	7	11 + barcodes	11 + barcodes	9 + barcodes
	Emulation	Epson LQ ESC/P2, IBM PPR X24/XL24	Epson LQ, IBM PPR X24E/X24E AGM	Epson LQ, IBM Proprinter or IBM Proprinter AGM	Epson LQ, IBM Proprinter III/AGM	Epson LQ, IBM PPR X24E/X24E AGM
	Standard interface	Parallel+USB	Parallel	Parallel+USB	Parallel+USB	Parallel+Serial
	Colour print	No	No	No	No	Standard on 395C

## 9-Pin Dot Matrix Printer range



		<b>ML280 Elite</b>	<b>ML320 Elite</b>	<b>ML3320</b>	<b>ML320FB</b>	<b>ML5520</b>		
<b>Narrow carriage</b>								
<b>Wide carriage</b>			<b>ML321 Elite</b>	<b>ML3321</b>		<b>ML5521</b>	<b>ML3410</b>	<b>ML4410</b>
<b>Print Head</b>	Number of pins	9	9	9	9	9	9	18 (2 X 9)
	Fastest print speed (cps)	375	360	435	360	570	550	1066
	Utility/LQ print speed at 10cpi (cps)	250/62.5	250/63	290/73	250/63	380/95	417/104	800/200
	Number of copies	1+3	1+4	1+4	1+4	1+5	1+7 (Bottom tractor)	1+9
	Resolution (dpi)	240 x 216	240 x 216	240 x 216	240 x 216	240 x 216	240 x 216	240 x 216
<b>Paper feed</b>	Feed method	Friction feed Platen pin feed	Friction feed Push tractor	Friction feed Push tractor	Friction feed Push tractor	Friction feed Push tractor	Friction feed Push tractor	Front push tractor Rear push tractor
	Tractor options	Top pull	Top pull Bottom push	Top pull Bottom push	Top pull Bottom push	Top pull Bottom push	Top pull Bottom push	N/A
	Cut sheet feeder options	Single bin	Single & dual	Single & dual	Single bin	Single & dual	Single & dual	N/A
<b>Column width (characters)</b>	Narrow carriage version at 10cpi	80	80	80	106	80	N/A	N/A
	Wide carriage version at 10cpi	N/A	136	136	N/A	136	136	136
	Compressed mode (narrow/wide)	160	160/272	160/272	212	160/272	272	272
<b>Interfaces &amp; Emulations</b>	Number of fonts	4 + barcodes	4	5 + barcodes	4	5 + barcodes	5 + barcodes	6 + barcodes
	Emulation	Epson LX, IBM Graphics or Oki Microline	Epson FX, IBM PPR/ Graphics or Oki Microline	Epson FX, IBM PPR/ Graphics, Oki Microline	Epson FX, IBM PPR	Epson FX, IBM PPR, Oki Microline	Epson FX, IBM PPR XL or Oki Microline/PM (optional)	Epson FX, IBM PPR, Oki Microline
	Standard interface	Parallel + USB	Parallel	Parallel	Parallel	Parallel + USB	Parallel+Serial	Parallel+Serial
	Colour print	No	No	No	No	No	No	No

**OKI EUROPE LTD.**  
 Central House, Balfour Road  
 Hounslow, Middlesex TW3 1HY  
 United Kingdom  
 T +44(0) 20 8219 2190  
 F +44(0) 20 8219 2199  
[WWW.OKIPRINTINGSOLUTIONS.COM](http://WWW.OKIPRINTINGSOLUTIONS.COM)



As an ENERGY STAR Partner, Oki has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

**OKI**  
 PRINTING SOLUTIONS